

Wide Format Laminiator

RSL-SERIES



- Ideal multi-function laminators for post-procedure of Signmaking and Digital print.
- Laser safety system
- Superior quality for hot & cold digital finishing (RSL-1120S is for Hot, Cold and Single Side lamination)
- Heavy duty durable silicone rubber
- Memory function (9 programs)
- Digital speed control : 9 settings up to 3m /min(Hot), 4m/min(Cold)
- STAND-BY function : Easy to operate and power saving
- Auto shut off
- Mounting up to 15mm

Description	RSL-1120	RSL-1120S	RSL-1400	RSL-1651
Power supply	AC 220~240V 50Hz			
Power consumption	2400 W	1200W	3300 W	3300 W
Max laminating width	1120mm / 44.1"		1400mm / 55"	1650mm / 65"
Film thickness	25 ~ 500mic / 1~20mil		50 ~ 500mic / 2~20mil	
De curling bar	No	Yes	No	
Max laminating speed	3m/min(Hot), 4m/min(Cold)			
Ready time	10min			
Heating method	Hot roller			
Drive motor	DC geared			
Max. temperature control	150°C / 302°F			
Speed control	9 settings			
Transport type	4 Roller			
Film core size	Metal 1",2",3"			
Cross cutter	NO			
Hot lamination	Yes			
Cold lamination	Yes			
Mounting thickness	15mm / 0.6"			
Roller diameter	80 mm			
Roller gap	1) Lamination, 2)1.0mm, 3) 5~7mm, 4) 10~13mm, 5) 15mm(open)			
Take up system	Chain link to main motor			
Reverse	Yes			
Remote control	Yes			
Foot pedal	Yes			
Unit dimensions (w x d x h)	1430 x 55 x 1120 (mm)		1710 x 550 x 1110 (mm)	1950 x 550 x 1110 (mm)
Unit weight	100kg		130kg / 286lbs	160kg / 354lbs
Carton dimensions (w x d x h)	1592 x 784 x1380 (mm)		1928 x 784 x1380 (mm)	2178 x 784 x1380 (mm)
Carton weight	200kg		230kg	230kg



RS Sovereign International Inc.

2 Volvo Drive, Rockleigh, NJ 07647 U.S.A.

TEL : +1) 800-397-1025

FAX : +1) 201-750-1022

www.royalsovereign.com